

30' Maxweld MAXCAT Walk Around Catamaran

Specifications:

- CENTER LINE LENGTH = 30' 10"
- OVERALL LENGTH = 33' 10" (INCLUDING SWIM STEP)
- BEAM = 12'
- CHINE BEAM = 10' 6"
- CONSTANT DEAD RISE BOTTOM, 18* AT TRANSOM, 36* AT POINT OF ENTRY
- DRAFT = 18" (DRIVES UP)
- FUEL CAPACITY = 250 GALLON (125 GALLONS PER SIDE)
- CENTER 24" TRANSOM DOOR
- SIDE HEIGHT = 66"
- BOTTOM THICKNESS = .250 (5086 MATERIAL)
- SIDE THICKNESS = .188 (5086 MATERIAL)

Features:

- WELDED ALUMINUM DECKS FROM 3/16" PLATE (5086 ALLOY)
- 5 STRINGER, HEAVY DUTY SUPER STRUCTURE PER HULL
- TRANSVERSE BULKHEADS 30" ON CENTERS (4- WATERTIGHT)
- MAXWELD CUSTOM BOW PULPIT WITH 6" UHMW BOW ROLLER AND 10" ALUMINUM CLEAT
- 8- 10" WELDED ALUMINUM CLEATS, STERN, MIDSHIP AND FORE
- BUILT IN FISH HOLDS
- CARPETED HEADLINERS AND SIDE WALLS WITH THERMAL INSULATION THROUGH OUT BOAT
- FULL WIDTH SWIM PLATFORM EXTENDS 36" FROM TRANSOM
- WATERTIGHT ENGINE HATCHES FLUSH WITH DECK
- COMPLETE SOUND INSULATION / VIBRATION DAMPENING SYSTEM
- COMPLETE 110 AND 12V MARINE ELECTRICAL SYSTEM WITH TINNED WIRING AND BLUE SEA BREAKER PANELS
- DIAMOND SEA GLAZE WATERTIGHT WINDOWS AND DOORS

**** FOR MORE DETAILED SPECS, PLEASE FILL OUT OUR INQUIRY FORM ****

SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE