

## **34' Maxweld Landing Cat**

### **Specifications:**

- CENTER LINE LENGTH = 34' 10"
- OVERALL LENGTH = 38' 10" (INCLUDING SWIM STEP)
- BEAM = 14'
- CHINE BEAM = 12' 9"
- CONSTANT DEAD RISE BOTTOM, 20\* AT TRANSOM, 36\* AT POINT OF ENTRY
- DRAFT = 20" (DRIVES UP)
- FUEL CAPACITY = 300 GALLONS (150 GALLONS PER SIDE)
- CENTER 24" TRANSOM DOOR
- SIDE HEIGHT = 72"
- BOTTOM THICKNESS = .250 (5086 MATERIAL)
- SIDE THICKNESS = .188 (5086 MATERIAL)

### **Features:**

- WELDED ALUMINUM, SELF BAILING DECKS WITH ANTI BACK FLOW SCUPPERS
- 5 STRINGER, HEAVY DUTY SUPER STRUCTURE PER HULL
- TRANSVERSE BULKHEADS 36" ON CENTER (5- WATERTIGHT)
- FOLDING BOW RAMP
- MAXWELD CUSTOM 6" ALUMINUM & UHMW BOW ROLLER WITH 10" ALUMINUM CLEAT
- 8- 10" WELDED ALUMINUM CLEATS, STERN, MIDSHIP AND FORE
- BUILT IN TRANSOM STORAGE BOXES
- CARPETED HEAD LINERS AND SIDE WALLS WITH THERMAL INSULATION THROUGH OUT
- FULL WIDTH SWIM PLATFORM EXTENDS 36" FROM TRANSOM
- WATERTIGHT ENGINE HATCHES FLUSH WITH DECK
- COMPLETE SOUND INSULATION / VIBRATION DAMPENING SYSTEM
- COMPLETE 110 AND 12V MARINE ELECTRICAL SYSTEM WITH TINNED WIRING AND BLUE SEA BREAKER PANELS
- DIAMOND SEA GLAZE WATERTIGHT WINDOWS AND DOORS

**\*\* FOR MORE DETAILED SPECS, PLEASE FILL OUT OUR INQUIRY FORM \*\***

***SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE***