

34' Maxweld Pilot House Catamaran

Specifications:

- CENTER LINE LENGTH = 34' 10"
- OVERALL LENGTH = 38' 4" (INCLUDING SWIM STEP)
- BEAM = 14'
- CHINE BEAM = 12' 9"
- CONSTANT DEAD RISE BOTTOM, 18* AT TRANSOM, 36* AT POINT OF ENTRY
- DRAFT = 20" (DRIVES UP)
- FUEL CAPACITY = 500 GALLONS (250 GALLONS PER SIDE)
- CENTER 24" TRANSOM DOOR
- SIDE HEIGHT = 72"
- BOTTOM THICKNESS = .250 (5086 MATERIAL)
- SIDE THICKNESS = .188 (5086 MATERIAL)

Features:

- WELDED ALUMINUM DECKS, SELF BAILING WITH ANTI BACK FLOW SCUPPERS
- 5 STRINGER, HEAVY DUTY SUPER STRUCTURE PER HULL
- TRANSVERSE BULKHEADS 30" ON CENTERS (5- WATER TIGHT)
- MAXWELD CUSTOM 6" ALUMINUM & UHMW BOW ROLLER WITH 10" ALUMINUM CLEAT
- 8- 10" WELDED ALUMINUM CLEATS, STERN, MIDSHIP AND FORE
- CARPETED HEAD LINER AND SIDE WALLS WITH THERMAL INSULATION THROUGH OUT BOAT
- BUILT IN FISH HOLDS
- WATERTIGHT ENGINE HATCHES FLUSH WITH DECK
- FULL WIDTH SWIM PLATFORM EXTENDS 42" FROM TRANSOM
- COMPLETE SOUND INSULATION / VIBRATION DAMPENING SYSTEM THROUGH OUT BOAT
- COMPLETE 110, 220, AND 12V MARINE ELECTRICAL SYSTEMS WITH TINNED WIRING AND BLUE SEA BREAKER PANELS
- DIAMOND SEA GLAZE WATERTIGHT WINDOWS AND DOORS

**** FOR MORE DETAILED SPECS, PLEASE FILL OUT OUR INQUIRY FORM ****

SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE