

## 40' Landing Cat

### Specifications:

- CENTER LINE LENGTH = 40' 10"
- OVERALL LENGTH = 43' 10" (INCLUDING SWIM STEP)
- BEAM = 15'
- CHINE BEAM = 13' 9"
- CONSTANT DEAD RISE BOTTOM, 20\* AT TRANSOM, 36\* AT POINT OF ENTRY
- DRAFT = 20" (DRIVES UP)
- FUEL CAPACITY = 500 GALLONS (250 GALLONS PER SIDE)
- CENTER TRANSOM DOOR
- SIDE HEIGHT = 72"
- BOTTOM THICKNESS = .250 (5086 MATERIAL)
- SIDE THICKNESS = .188 (5086 MATERIAL)

### Features:

- WELDED ALUMINUM, SELF BAILING DECKS WITH ANTI BACK FLOW SCUPPERS
- 5 STRINGER, HEAVY DUTY SUPER STRUCTURE PER HULL
- TRANSVERSE BULKHEADS ON 36" CENTERS (5- WATER TIGHT)
- MAXWELD CUSTOM 6" ALUMINUM & UHMW BOW ROLLER WITH 10" ALUMINUM CLEAT
- 8- 10" WELDED ALUMINUM CLEATS, STERN, MIDSHIP AND FORE
- FOLDING BOW RAMP
- CARPETED HEAD LINERS AND SIDE WALLS WITH THERMAL INSULATION THROUGH OUT BOAT
- BUILT IN TRANSOM STORAGE BOXES
- FULL WIDTH SWIM PLATFORM EXTENDS 36" FROM TRANSOM
- WATERTIGHT ENGINE HATCHES FLUSH WITH DECK
- COMPLETE SOUND INSULATION / VIBRATION DAMPENING SYSTEM THROUGH OUT BOAT
- COMPLETE 110 AND 12V MARINE ELECTRICAL SYSTEM WITH TINNED WIRING AND BLUE SEA BREAKER PANELS
- DIAMOND SEA GLAZE WATERTIGHT WINDOWS AND DOORS

**\*\* FOR MORE DETAILED SPECS, PLEASE FILL OUT OUR INQUIRY FORM \*\***

***SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE***