

## **40' Maxweld Pilot House Catamaran**

### **Specifications:**

- CENTER LINE LENGTH = 40' 10"
- OVERALL LENGTH = 44' 4" (INCLUDING SWIM STEP)
- BEAM = 15'
- CHINE BEAM = 13' 9"
- CONSTANT DEAD RISE BOTTOM, 20\* AT TRANSOM, 36\* AT POINT OF ENTRY
- DRAFT = 20" (DRIVES UP)
- FUEL CAPACITY = 500 GALLONS (250 GALLONS PER SIDE)
- CENTER 24" TRANSOM DOOR
- SIDE HEIGHT = 72"
- BOTTOM THICKNESS = .250 (5086 MATERIAL)
- SIDE THICKNESS = .188 (5086 MATERIAL)

### **Features:**

- WELDED ALUMINUM, SELF BAILING DECKS WITH ANTI BACK FLOW SCUPPERS
- 5 STRINGER, HEAVY DUTY SUPER STRUCTURE PER HULL
- TRANSVERSE BULKHEADS 30" ON CENTERS (5- WATER TIGHT)
- MAXWELD CUSTOM 6" ALUMINUM & UHMW BOW ROLLER WITH 10" ALUMINUM CLEAT
- 8- 10" WELDED ALUMINUM CLEATS, STERN, MIDSHIP AND FORE
- BUILT IN FISH HOLDS
- CARPETED HEAD LINERS AND SIDE WALLS WITH THERMAL INSULATION THROUGH OUT BOAT
- FULL WIDTH SWIM PLATFORM EXTENDS 42" FROM TRANSOM
- WATERTIGHT ENGINE HATCHES FLUSH WITH DECK
- COMPLETE SOUND INSULATION / VIBRATION DAMPENING SYSTEM THROUGH OUT BOAT
- COMPLETE 110, 220, AND 12V MARINE ELECTRICAL SYSTEMS WITH TINNED WIRING AND BLUE SEA BREAKER PANELS
- DIAMOND SEA GLAZE WATERTIGHT WINDOWS AND DOORS

**\*\* FOR MORE DETAILED SPECS, PLEASE FILL OUT OUR INQUIRY FORM \*\***

***SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE***